Safety data sheet according to 1907/2006/EC, Article 31



Printing date 12.10.2013

Revision: 13.08.2012

| Printing date | 12.10.2013 Revision: 13.08.2012 |
|---|--|
| 1 Produc | ct and Company Identification |
| · Product | identifier THINNERS |
| · Trade na | ame: <u>S50 P.U. THINNER EXTRA SLOW</u> |
| · Relevan Use as p | number: S50 t identified uses of the substance or mixture and uses advised against paint reducer tion of the substance / the preparation refer to the relevant Technical Data Sheet |
| General | of the supplier of the safety data sheet Paint Co. S.A.L Department- |
| www.gen • Manufac General I TURBO P.O. Box Beirut LEBANO | |
| | information obtainable from: Product safety department ncy telephone number: During normal opening times: (961) 9 925990 /1/2 |
| 2 Hazard | Is identification |
| · Classific | cation of the substance or mixture |
| | cation according to Directive 67/548/EEC or Directive 1999/45/EC Harmful |
| R65: | Harmful: may cause lung damage if swallowed. |
| 🗙 Xi; I | Irritant |
| R37: | Irritating to respiratory system. |
| 1 N; E | Dangerous for the environment |
| R51/53: | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| The proc guideline · Classific | Flammable. tion concerning particular hazards for human and environment: duct has to be labelled due to the calculation procedure of the "General Classification for preparations of the EU" in the latest valid version. cation system: sification is according to the latest editions of the EU-lists, and extended by company and data. |
| · Label ele | ements |
| · Labelling The proc | g according to EU guidelines: duct has been classified and marked in accordance with EU Directives / Ordinance on us Materials. |

· Code letter and hazard designation of product:



Xn Harmful N Dangerous for the environment

(Contd. on page 2)



Printing date 12.10.2013

Revision: 13.08.2012

Trade name: S50 P.U. THINNER EXTRA SLOW

(Contd. of page 1)

• Hazard-determining components of labelling: Solvent naphtha (petroleum), light arom.

· Risk phrases:

10 Flammable.

- 37 *Irritating to respiratory system.*
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.

· Safety phrases:

- 1/2 Keep locked up and out of the reach of children.
- 9 Keep container in a well-ventilated place.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| • | components: | | |
|------------|--|---|---------|
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | Xi R37 R10 | 25-50% |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | R10 | 25-50% |
| 112-07-2 | 2-butoxyethyl acetate | 🗙 Xn R20/21 | 2.5-10% |
| 1330-20-7 | xylene | Xn R20/21; <mark>x</mark> Xi R38 R10 | 2.5-10% |

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
 No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2013

Revision: 13.08.2012

(Contd. of page 2)

Trade name: S50 P.U. THINNER EXTRA SLOW

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
 Information about fire and explanation protection
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

| | Exposure contro | ICIDOKC | han al r | Kotootion |
|------------|-----------------|---------|----------|-----------|
| (n 1 | | | | |
| . <i>•</i> | | | | |
| | | | | |

• Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

| Ingredients | with limit values that require monitoring at the workplace: |
|---------------------------------|--|
| | methoxy-1-methylethyl acetate |
| IOELV (EU) | Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin |
| 112-07-2 2-1 | butoxyethyl acetate |
| IOELV (EU) | Short-term value: 333 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Skin |
| | (Contd. on page 4) |

LB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2013

Revision: 13.08.2012

Trade name: S50 P.U. THINNER EXTRA SLOW

| | (Contd. of page |
|------------------------------|--|
| 1330-20-7 x | - |
| IOELV (EU) | Short-term value: 442 mg/m ³ , 100 ppm |
| | Long-term value: 221 mg/m³, 50 ppm |
| | Skin |
| Additional i | information: The lists valid during the making were used as basis. |
| Exposure c | |
| | rotective equipment: |
| | otective and hygienic measures: |
| | from foodstuffs, beverages and feed. |
| | remove all soiled and contaminated clothing |
| | s before breaks and at the end of work. |
| | v protection: |
| | rief exposure or low pollution use respiratory filter device. In case of intensive or long |
| | e self-contained respiratory protective device. |
| Protection of | |
| | material has to be impermeable and resistant to the product/ the substance/ i |
| preparation. | |
| | sing tests no recommendation to the glove material can be given for the product/ |
| | the chemical mixture. |
| | the glove material on consideration of the penetration times, rates of diffusion and |
| degradation Material of g | nlovos |
| | n of the suitable gloves does not only depend on the material, but also on further ma |
| | nd varies from manufacturer to manufacturer. As the product is a preparation of seve |
| | the resistance of the glove material can not be calculated in advance and has therefore |
| | ed prior to the application. |
| | time of glove material |
| | reak through time has to be found out by the manufacturer of the protective gloves a |
| has to be ob | |
| Eye protect | |
| , - <u>-</u> | |
| | |
| 🛛 🗐 🐨 🖉 Tiệ | ghtly sealed goggles |
| | |

| Information on basic physical and General Information Appearance | chemical properties | |
|--|---------------------|--|
| Appearance: Form: | Liquid | |
| Colour: | Clear | |
| · Odour: | Characteristic | |
| Odour threshold: | Not determined. | |
| · pH-value: | Not determined. | |
| · Change in condition | | |
| Melting point/Melting range: | Undetermined. | |
| Boiling point/Boiling range: | 124 °C | |
| Flash point: | 25 °C | |
| · Flammability (solid, gaseous): | Not applicable. | |
| · Ignition temperature: | 280 °C | |



Printing date 12.10.2013

Revision: 13.08.2012

Trade name: S50 P.U. THINNER EXTRA SLOW

| | (Contd. of page 4 |
|--|---|
| · Decomposition temperature: | Not determined. |
| · Self-igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: | |
| Lower: | 0.7 Vol % |
| Upper: | 10.8 Vol % |
| · Vapour pressure at 20 °C: | 5 hPa |
| · Density at 20 °C: | 0.907 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/v | vater): Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 100.0 % |
| VOC (EC) | 907.0 g/l |
| Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

| | LD50 | >6800 mg/kg (rat) |
|------------|----------|-------------------|
| Dermal | LD50 | >3400 mg/kg (rab) |
| Inhalative | LC50/4 h | >10.2 mg/l (rat) |

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 6)



Printing date 12.10.2013

Revision: 13.08.2012

Trade name: S50 P.U. THINNER EXTRA SLOW

(Contd. of page 5)

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

2 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| UN-Number | | |
|----------------------------|----------------------|--|
| ADR, IMDG, IATA | UN1263 | |
| UN proper shipping name | | |
| ADR | 1263 PAINT | |
| IMDG, IATA | PAINT | |
| Transport hazard class(es) | | |
| ADR, IMDG, IATA | | |
| | | |
| | | |
| Class | 3 Flammable liquids. | |
| Label | 3 | |



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2013

Revision: 13.08.2012

Trade name: S50 P.U. THINNER EXTRA SLOW

| | (Contd. of pag |
|--|-----------------------------|
| · Packing group | |
| · ADR, IMDG, IATA | III |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids. |
| · Danger code (Kemler): | 30 |
| · EMŠ Number: | F-E, <u>S-E</u> |
| · Transport in bulk according to Annex | ll of |
| MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Transport category | 3 |
| · Tunnel restriction code | D/E |

15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R37 Irritating to respiratory system.

R38 Irritating to skin.

· Department issuing MSDS: Product safety department

· Contact: Ms. Topaljikian