

Printing date 12.10.2013 Revision: 13.08.2012

1 Product and Company Identification

· Product identifier THINNERS

· Trade name: S21 P.U.THINNER SLOW

· Article number: S21

· Relevant identified uses of the substance or mixture and uses advised against Use as paint reducer

- · Application of the substance / the preparation refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

General Paint Co. S.A.L

-Safety Department-

For further information, please consult our Intenet site www.generalpaint.biz

· Manufacturer/Supplier:

General Paint Co. SAL

TURBO

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: (961) 9 925990 /1/2

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20: Harmful by inhalation.



💢 Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.



F; Highly flammable

R11: Highly flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





Xn Harmful F Highly flammable

· Hazard-determining components of labelling: methyl isobutyl ketone

(Contd. on page 2)



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: S21 P.U.THINNER SLOW

(Contd. of page 1)

xylene

· Risk phrases:

11 Highly flammable.

20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

· Safety phrases:

- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

- 46 If swallowed, seek medical advice immediately and show this container or label.
- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerou	s components:	
	methyl isobutyl ketone Xn R20; Xi R36/37; FR11 R66	25-50%
1330-20-7	xylene Xn R20/21; Xi R38 R10	25-50%
108-65-6	2-methoxy-1-methylethyl acetate R10	25-50%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

LB



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: S21 P.U.THINNER SLOW

(Contd. of page 2)

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: S21 P.U.THINNER SLOW

(Contd. of page 3)

· Control parameters

Ingredients with limit values that require monitoring at the workplace:

methyl isobutyl ketone

IOELV (EU) Short-term value: 208 mg/m³, 50 ppm

Long-term value: 83 mg/m³, 20 ppm

1330-20-7 xylene

IOELV (EU) Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

108-65-6 2-methoxy-1-methylethyl acetate

IOELV (EU) Short-term value: 550 mg/m³, 100 ppm

Long-term value: 275 mg/m³, 50 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: S21 P.U.THINNER SLOW

(Contd. of page 4)

9 Physical and chemical prope	erties
· Information on basic physical and · General Information	chemical properties
· Appearance:	
Form:	Fluid
Colour: · Odour:	Clear
· Odour :	Characteristic Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	115 °C
Flash point:	14 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 ℃
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosair/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.8 Vol %
· Vapour pressure at 20 °C:	8 hPa
· Density at 20 °C:	0.8792 g/cm³
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wa	ter): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	879.2 g/l
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: S21 P.U.THINNER SLOW

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values rel	evant for classification:
methyl is	obutyl ket	one
Oral	LD50	2080 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)
1330-20-7	xylene	
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: S21 P.U.THINNER SLOW

(Contd. of page 6)

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

Transport information		
UN-Number ADR, IMDG, IATA	UN1263	
UN proper shipping name		
ADR	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)		
ADR, IMDG, IATA		
Class Label	3 Flammable liquids. 3	
Packing group ADR, IMDG, IATA	II	
Environmental hazards:	<i>"</i>	
Environmental nazaros: Marine pollutant:	No	
•		
Special precautions for user	Warning: Flammable liquids.	
Danger code (Kemler): EMS Number:	33 <i>F-E</i> ,S-E	
Transport in bulk according to Annex		
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		

15 Regulatory information

· Tunnel restriction code

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

D/E

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

R20/21 Harmful by inhalation and in contact with skin.

R36/37 Irritating to eyes and respiratory system.

R38 Irritating to skin.

(Contd. on page 8)

(Contd. of page 7)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2013 Revision: 13.08.2012

Trade name: S21 P.U.THINNER SLOW

R66 Repeated exposure may cause skin dryness or cracking.

· Department issuing MSDS: Product safety department

· Contact: Ms. Topaljikian

I B