Printing date 26.10.2013

TURBO

Revision: 26.10.2013

| 1 Product and Company Identification | |
|--|-----------------|
| · Product identifier THINNERS | |
| · Trade name: <u>S23 P.U. THINNER SLOW</u> | |
| Article number: S23 Relevant identified uses of the substance or mixture and uses advised against Use as paint reducer Application of the substance / the preparation refer to the relevant Technical Data SI | heet |
| • Details of the supplier of the safety data sheet General Paint Co. S.A.L -Safety Department- | |
| For further information, please consult our Internet site www.generalpaint.biz • Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@generalpaint.biz | |
| Further information obtainable from: Product safety department Emergency telephone number: During normal opening times: (961) 9 925990 /1/2 | |
| 2 Hazards identification | |
| · Classification of the substance or mixture | |
| | |
| Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xn; Harmful | |
| R20/21: Harmful by inhalation and in contact with skin. | |
| Xi; Irritant | |
| | |
| R38: Irritating to skin. | |
| R10: Flammable. Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Consumer of the product has to be labelled due to the calculation procedure of the "General Consumer of the product has to be labelled due to the latest valid version. Classification system: The classification is according to the latest editions of the EU-lists, and extended by consistent data. | |
| · Label elements | |
| Labelling according to EU guidelines: The product has been classified and marked in accordance with EU Directives / Or Hazardous Materials. | rdinance on |
| · Code letter and hazard designation of product: | |
| Xn Harmful | |
| · Hazard-determining components of labelling: xylene | |
| · Risk phrases: | |
| 10 Flammable. 20/21 Harmful by inhalation and in contact with skin. | |
| | ntd. on page 2) |

Printing date 26.10.2013

Revision: 26.10.2013

(Contd. of page 1)

Trade name: S23 P.U. THINNER SLOW

38 Irritating to skin.

- · Safety phrases:
- 2 Keep out of the reach of children.
- 36/37 Wear suitable protective clothing and gloves.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 56 Dispose of this material and its container to hazardous or special waste collection point.
- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

108-65-6 2-methoxy-1-methylethyl ac 1330-20-7 xylene

| ethylethyl acetate | R10 | 25-50% |
|--------------------|------------------------------|--------|
| | 🗙 Xn R20/21; 🔀 Xi R38 R10 | 25-50% |

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· Description of first aid measures

- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

[•] Environmental precautions: Do not allow to enter sewers/ surface or ground water.

LB

Printing date 26.10.2013

Revision: 26.10.2013

(Contd. of page 2)

Trade name: S23 P.U. THINNER SLOW

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. 7 Handling and storage · Handling: Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. · Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. · Conditions for safe storage, including any incompatibilities · Storage: · Requirements to be met by storerooms and receptacles: No special requirements. Information about storage in one common storage facility: Not required. Further information about storage conditions: Keep container tightly sealed. · Storage class: 3 · Specific end use(s) No further relevant information available. 8 Exposure controls/personal protection · Additional information about design of technical facilities: No further data; see item 7. · Control parameters · Ingredients with limit values that require monitoring at the workplace: 108-65-6 2-methoxy-1-methylethyl acetate IOELV (EU) Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin

1330-20-7 xylene

IOELV (EU) Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin

• Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

I B

Printing date 26.10.2013

Revision: 26.10.2013

(Contd. of page 3)

Trade name: S23 P.U. THINNER SLOW

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

| 9 Physical and chemical prope | erties |
|---|---|
| Information on basic physical and General Information | chemical properties |
| · Appearance: Form: | Fluid |
| Colour: | Clear |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| Change in condition Melting point/Melting range: Boiling point/Boiling range: | Undetermined. 124 °C |
| · Flash point: | 25 ℃ |
| · Flammability (solid, gaseous): | not applicable |
| · Ignition temperature: | 315 °C |
| · Decomposition temperature: | Not determined. |
| · Self-igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 10.8 Vol % |
| · Vapour pressure at 20 °C: | 10.7 hPa |
| · Density at 20 °C: | 0.9056 g/cm³ |
| | (Contd. on page 5 |

LB



Printing date 26.10.2013

Revision: 26.10.2013

Trade name: S23 P.U. THINNER SLOW

| | | (Contd. of page |
|------------------------------------|--|-----------------|
| · Relative density | Not determined. | |
| · Vapour density | Not determined. | |
| · Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with | | |
| water: | Not miscible or difficult to mix. | |
| · Partition coefficient (n-octanol | /water): Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| · Solvent content: | | |
| Organic solvents: | 100.0 % | |
| VÕC (EC) | 905.6 g/l | |
| · Other information | No further relevant information available. | |

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values relevant for classification:

1330-20-7 xylene

- Oral LD50 4300 mg/kg (rat)
- Dermal LD50 2000 mg/kg (rabbit)
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information: The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful Irritant

2 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 6)

LB ·

Printing date 26.10.2013

Revision: 26.10.2013

(Contd. of page 5)

Trade name: S23 P.U. THINNER SLOW

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

| UN-Number | | |
|--------------------------------------|-----------------------------|--|
| ADR, IMDG, IATA | UN1263 | |
| UN proper shipping name | | |
| ADR | 1263 PAINT | |
| IMDG, IATA | PAINT | |
| Transport hazard class(es) | | |
| ADR, IMDG, IATA | | |
| | | |
| Class | 3 Flammable liquids. | |
| Label | 3 | |
| Packing group | | |
| ADR, IMDG, IATA | <i>III</i> | |
| Environmental hazards: | | |
| Marine pollutant: | No | |
| Special precautions for user | Warning: Flammable liquids. | |
| Danger code (Kemler): | 30 | |
| EMS Number: | F-E, <u>S-E</u> | |
| Transport in bulk according to Annex | ll of | |
| MARPOL73/78 and the IBC Code | Not applicable. | |
| Transport/Additional information: | | |
| ADR | | |
| Limited quantities (LQ) | 5L | |
| Transport category | 3 | |

(Contd. on page 7)

TURBO

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.10.2013

Revision: 26.10.2013

Trade name: S23 P.U. THINNER SLOW

(Contd. of page 6)

15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.R38 Irritating to skin.

- · Department issuing MSDS: Product safety department
- · Contact: Ms. Topaljikian