

Printing date 12.10.2013 Revision: 13.08.2012

## 1 Product and Company Identification

· Product identifier CLEARS

· Trade name: C050 SUPER FAST CLEAR

· Article number: C050

- · Relevant identified uses of the substance or mixture and uses advised against use as paint clear over base
- · Application of the substance / the preparation refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

General Paint Co. S.A.L. -Safety Department-

For further information, please consult our Internet site www.generalpaint.biz

Manufacturer/Supplier:

General Paint Co. SAL

**TURBO** 

P.O. Box 7623

Beirut

**LEBANON** 

info@generalpaint.biz

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: (961) 9 925990 /1/2

### Hazards identification

- · Classification of the substance or mixture
- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R63: Possible risk of harm to the unborn child.



F; Highly flammable

Highly flammable. R11:

R52/53-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





Xn Harmful Highly flammable

· Hazard-determining components of labelling: toluene

(Contd. on page 2)



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: C050 SUPER FAST CLEAR

(Contd. of page 1)

## · Risk phrases:

- 11 Highly flammable.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 63 Possible risk of harm to the unborn child.
- 67 Vapours may cause drowsiness and dizziness.

### Safety phrases:

- 2 Keep out of the reach of children.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 36/37 Wear suitable protective clothing and gloves.
- 46 If swallowed, seek medical advice immediately and show this container or label.

#### · Special labelling of certain preparations:

Contains neodecansäureglycidylester, 2-hydroxyethyl methacrylate, methyl methacrylate, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate, s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-butyl-4-hydroxyphenyl)propionyl-o-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene). May produce an allergic reaction.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
108-88-3	toluene Xn R48/20-63-65;  Xi R38;  FR11 R67 Repr. Cat. 3	2.5-10%	
108-65-6	2-methoxy-1-methylethyl acetate R10	½ 2.5%	
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate  Xi R43; 🜇 N R50/53	½ 2.5%	
80-62-6	methyl methacrylate  Xi R37/38; Xi R43;  F R11	½ 2.5%	
4008-30-7	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-butyl-4-hydroxyphenyl)propionyl-o-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)  Xi R43; N R51/53	½ 2.5%	
26761-45-5	neodecansäureglycidylester  Xi R38; Xi R43; N R51/53	½ 2.5%	
82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate Xi R43; 🜇 N R50/53	½ 2.5%	
868-77-9	2-hydroxyethyl methacrylate	½ 2.5%	

· Additional information: For the wording of the listed risk phrases refer to section 16.

LB



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: C050 SUPER FAST CLEAR

(Contd. of page 2)

## 4 First aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 4)



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: C050 SUPER FAST CLEAR

(Contd. of page 3)

#### · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 108-65-6 2-methoxy-1-methylethyl acetate

IOELV (EU) Short-term value: 550 mg/m³, 100 ppm

Long-term value: 275 mg/m³, 50 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: C050 SUPER FAST CLEAR

(Contd. of page 4)

9 Physical and chemical prop	erties			
· Information on basic physical and	chemical properties			
· General Information	<i>,</i> .			
· Appearance:				
Form:	Liquid			
Colour:	Clear			
· Odour:	Characteristic			
· Odour threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	110 ℃			
· Flash point:	4 °C			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	370 °C			
· Decomposition temperature:	Not determined.			
· Self-igniting:	Product is not selfigniting.			
· Danger of explosion:	Product is not explosive. However, formation of explosivair/vapour mixtures are possible.			
· Explosion limits:				
Lower:	1.2 Vol %			
Upper:	7.5 Vol %			
· Vapour pressure at 20 °C:	10.7 hPa			
Density at 20 °C:	0.98 g/cm³			
· Relative density	Not determined.			
· Vapour density	Not determined.			
· Evaporation rate	Not determined.			
· Solubility in / Miscibility with				
water:	Not miscible or difficult to mix.			
· Partition coefficient (n-octanol/water): Not determined.				
· Viscosity:				
Dynamic:	Not determined.			
Kinematic:	Not determined.			
· Solvent content:				
Organic solvents:	53.1 %			
VOC (EC)	520.3 g/l			
Solids content:	45.6 %			
· Other information	No further relevant information available.			

#### 10 Stability and reactivity

- Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

(Contd. on page 6)



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: C050 SUPER FAST CLEAR

(Contd. of page 5)

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

### · LD/LC50 values relevant for classification:

#### 108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

## 12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

LB



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: C050 SUPER FAST CLEAR

(Contd. of page 6)

Transport information	
UN-Number	
ADR, IMDG, IATA	UN3286
UN proper shipping name	
ADR	3286 FLAMMABLE LIQUID, TOXIC, CORROSIN
IMDC IATA	N.O.S. (TOLUENE, cellulose acetate butyrate) FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O
IMDG, IATA	(TOLUENE, cellulose acetate butyrate)
Transport hazard class(es)	, - ,
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3+6.1+8
Packing group	
ADR, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	368
EMS Number:	F-E,S-C
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D/E

## 15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

R10 Flammable.

R11 Highly flammable.

R36/38 Irritating to eyes and skin.

R37/38 Irritating to respiratory system and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 8)



Printing date 12.10.2013 Revision: 13.08.2012

Trade name: C050 SUPER FAST CLEAR

(Contd. of page 7)

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R63 Possible risk of harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.R67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: Product safety department

· Contact: Ms. Topaljikian

LB ·